

RC70c4



Specifications:

Channels	no	4
Class	Type	AB
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	4x 68
@ 2 ohm stereo:	Wrms	4x 105
@ 4 ohm mono:	Wrms	2x 210
Operation supply	V	10 -16
Thermal protection	°C	80
THD @ 4 Ω / 50% Pmax	%	0.5
Signal/noise	dB	95
Band width +- 1 dB	Hz	20-20000
Input sensitivity	Vrms	0.2-10
Low input impedance	Ω	5k
High input impedance	Ω	50(with RC-HLT)
Damping @ 80 Hz		50
Power consumption, idle	A	0.75
Power cons. 4 Ω stereo	A	29
Power cons. 4 Ω bridged	A	47
Power cons. 2 Ω stereo	A	47
Weight	kg	2.20
Dimensions	l/w/h	283/150/50mm

Features:

- *Input with low- or high-level signal*
- *Stable at 2ohm stereo per channel and 4ohm bridge mode*
- *High-level with autosense function (no remote signal required)*
- *Variable switchable Low Pass Filter from 45 to 225 Hz*
- *Variable switchable High Pass Filter from 45 to 225 Hz*

Miscellaneous:

- Protection for overheating, overloading, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink